

# The Focus Is On Powerful Optical 5.7x Zoom

At 28mm, you get extraordinary wideangle picture that you'll never produce with a conventional 35 mm lens. The optical 5.7x zoom draws distant subjects close up, capturing all the beautiful details.



### 28mm wide angle

Thanks to Ricoh's original Double Retracting LENS System, a high-quality lens unit fits inside an amazingly compact camera. The Caplio R30 holds an optical 5.7x zoom extending from wideangle 28mm to 160mm telephoto. The advanced technology inside continues with a 5.13 effective megapixel CCD that delivers faithful reproduction of colors and textures. This Caplio offers it all. Brilliant image quality. Unique 28mm pictures. Wide-range zoom versatility. Plus, 1cm macro shooting.



160mm telephoto

- 28-160mm optical 5.7x zoom
- Effective megapixel 5.13 CCD
- Top shutter release time lag: 0.007 sec.\*2
- 1cm macro

\* 1 Number of shots measured using CIPA standard parameters. Actual performance may vary according to usage conditions.
\* 2 Shutter release time lag with focus lock engaged.
& Focal lengths are 35mm film camera equivalents.

## **Our Innovative Technology Keeps Shrinking**

#### Astonishing macro shots from 1cm away

Move in and shoot as close as 1cm away from your subject with the lens set at its widest angle, or 8cm away in telemacro. You can use AF Target Selection with its four direction buttons— ▲▼◀▶ —to shift the focus point without moving the camera. Explore the fun world of macro photography!



• 0.007-second shutter release time lag\*

The Caplio R30 powers up in just 1.1 seconds, has a shutter release time lag of

Champagne

approximately 0.09 seconds (without focus lock engaged) and resets for your next shot in half a second. Enjoy fast response that lets you take great shot after shot.

\* Approx. time with focus lock engaged % Time measurements with flash OFF

#### Compact design and long-lasting power

With the included rechargeable lithium-ion battery, you can shoot approximately 330 pictures\*. That's enough for an entire vacation, or business trip. Synchro monitor mode automatically switches the LCD monitor off when the camera is not in use, delivering a big gain in battery power conservation.



rgeable lithium-ion battery

\*Number of shots measured using CIPA standard parameters Actual performance may vary according to usage conditions

• Double Retracting LENS System makes room for the optical 5.7x zoom

Ricoh's original Double Retracting LENS System swings part of the lens group like a pendulum inside the camera when the lens retracts. This enables a 5.7x optical zoom range-wide-angle 28mm to 160mm zoom -to fit inside the Caplio R30's slim 26mm body.



Double Retracting LENS System

- Additional features & functions • Skew correction function—handy for
  - business uses
  - Eight scene modes
  - Three continuous shooting modes
  - Shoot video with digital zoom and sound until memory is full

#### Caplio R30 Major Specifications

Item	Description
CCD	Effective 5.13 million pixels (5.25 million square pixels), 1/2.5-inch primary-color CCD
Lens	Focal length f: 4.6-26.4mm (equivalent to 28-160mm for 35mm film cameras)
	Step-zoom intervals: 7 steps (28mm, 35mm, 50mm, 85mm, 105mm, 135mm,
	160mm)
	Aperture F: 3.3 (W)-4.8 (T)
Recording Mode	Still (Continuous, S-Continuous, M-Continuous),
	Scene (Portrait, Sports, Landscape, Night Scene, Skew correction, Text, Zoom Macro,
	High-Sensitivity), Motion, Sound
Recording Media	SD Memory Card™(32/64/128/256/512MB/1GB), Multi Media Card™,
	Built-in Memory 26MB
LCD Monitor	2.5" translucent amorphous silicon TFT LCD (approx. 114,000 pixels)
Dimensions (W x D x H)	95.0 x 26.0 x 53.0mm (excluding projections)
Weight	Approx. 135g (excluding battery, SD Memory Card, hand strap)
	Accessories (battery, hand strap) approx. 30g
Power Source	rechargeable battery (DB-60) x 1, AC adaptor (AC-4c)

#### Caplio R30 Optional Accessories

For more information, visit:

	Accessory Name
Rechargeable Lithium-Ion Battery: DB-60	
Battery Charger: BJ-6	
AC Adapter: AC-4c	
	Soft Case: SC-60

http://www.ricohpmmc.com

#### (Accessories Included) ①USB Cable 3 2 AV Cable ③ CD-ROM ④ Hand Strap 6 Rechargeable Lithium-Ion Battery: DB- 60 6 Battery Charger: BJ-6 Instruction Manuals (Camera, Introduction)\* Warranty Card \* Software manual supplied on CD-ROM

 Caplio is the registered trademark of Ricoh Co., Ltd.
Microsoft, Windows and Direct X are registered trademarks or trademarks of Microsoft Corporation in the U.S. and/or other countries.
Apple, Macintosh and Mac OS are registered trademarks or trademarks of Apple Computer Inc. in the U.S. and/or other countries.
The SD logo is a trademark.
Compatible with EPSON PRINT Image Matching III.
All other trademarks mentioned herein are the property of their respective SictBridge Exif Print

RICOH

RICOH COMPANY, LTD. 3-2-3.Shin-vokohama Kohoku-ku,Yokohama-shi 222-8530,Japan Phone: 045-477-1738 Fax: 045-477-1797 http://www.ricoh.com/r\_dc RICOH EUROPE B.V. (PMMC EUROPE) Oberrather Straße 6, D-40472 Düsseldorf, Germany Phone:0211-6546-0 Fax:0211-6546-308 http://www.ricohpmmc.com RICOH UK LTD. (PMMC UK) RICOH Ukse, 1 Plane Tree Crescent, Feltham, Middlesex, TW13 7HG, England Phone:0208-261-4000 Fax:0208-261-4220

RICOH FRANCE S.A. (PMMC FRANCE) 383. Avenue du Général de Gaulle - BP 307-931-13 Clamart Cédex, France Phone:01-4094-3267 Fax:01-4094-3276 RICOH ESPANA, S.A. (PMMC SPAIN) Av. Litoral Mar, 12-14, 08005 Barcelona, Spain Phone: 093-295-7600 Fax:093-295-7605 RICOH EUROPE B.V. (PMMC BENELUX) Koolhovenlaan 35, 1119 NB Schiphol- Rijk, The Netherlands Phone: 020-5474111 Fax: 020-5474540

Black

RICOH ITALIA S.p.A. (PMMC ITALY) via Ponchielli, 3 20063 Cernusco S/N Milano, Italy Phone: +39-02-92361217 Fax: +39-02-92361244 RICOH HONG KONG LIMITED Personal Multimedia Products Center 21/F., Tai Yau Building, 181 Johnston Road, Wan Chai, Hong Kong Phone: 2862-2888 Fax: 2566-3647/2866-1120 RICOH AUSTRALIA PTY. LTD. 8 Rodboruogh Road, Frenchs Forrest,N.S.W. 2086 Phone:02-8977-1111 Fax:02-8977-1100 http://www.ricoh.com.au

RICOH CORPORATION 5 Dedrick Place West Caldwell, NJ 07006 U.S.A. Phone: 1-800-Ricoh93 http://www.ricoh-usa.com

000	Encentre of to minion pixels (0.20 minion square pixels), fized mon primary color con
Lens	Focal length f: 4.6-26.4mm (equivalent to 28-160mm for 35mm film cameras)
	Step-zoom intervals: 7 steps (28mm, 35mm, 50mm, 85mm, 105mm, 135mn
	160mm)
	Aperture F: 3.3 (W)-4.8 (T)
Recording Mode	Still (Continuous, S-Continuous, M-Continuous),
	Scene (Portrait, Sports, Landscape, Night Scene, Skew correction, Text, Zoom Macro
	High-Sensitivity), Motion, Sound
Recording Media	SD Memory Card™(32/64/128/256/512MB/1GB), Multi Media Card™,
	Built-in Memory 26MB
LCD Monitor	2.5" translucent amorphous silicon TFT LCD (approx. 114,000 pixels)
Dimensions (W x D x H)	95.0 x 26.0 x 53.0mm (excluding projections)
Weight	Approx. 135g (excluding battery, SD Memory Card, hand strap)
	Accessories (battery hand strap) approx 30g